

S5-GC(15-23)K-LV

Solis Three Phase Inverters

Efficient

- Max. efficiency 97.8%
- String current up to 16A
- 3 MPPT design, supports multiple orientation system design
- Night time PID recovery function, increases overall system yield (optional)
- Wide voltage range and low startup voltage

Smart

- Supports export power control
- Intelligent string monitoring, smart I-V curve scan
- Supports RS485, WiFi, GPRS
- Scan to register on SolisCloud, supports remote upgrade and control

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life
- Intelligent redundant fan-cooling

Economic

- Supports GPRS/WiFi communication with less wiring and reduced installation costs
- > 150% DC/AC ratio
- Supports high power modules for lower installation costs
- Supports aluminium wire access to reduce cost

Models:

S5-GC15K-LV

S5-GC20K-LV

S5-GC23K-LV



360° View

DATASHEET

S5-GC(15-23)K-LV

Models	15K	20K	23K
Input DC			
Recommended max. PV power	22.5 kW	30 kW	34.5 kW
Max. input voltage	1100 V		
Rated voltage	600 V		
Start-up voltage	180 V		
MPPT voltage range	200-1000 V		
Max. input current	32 A / 32 A / 32 A		
Max. short circuit current	40 A / 40 A / 40 A		
MPPT number/Max. input strings number	3/6		
Output AC			
Rated output power	15 kW	20 kW	23 kW
Max. apparent output power	16.5 kVA	22 kVA	25 kVA
Max. output power	16.5 kW	22 kW	25 kW
Rated grid voltage	3/PE, 220 V		
Rated grid frequency	50 Hz / 60 Hz		
Rated grid output current	39.4 A	52.5 A	60.4 A
Max. output current	43.3 A	57.7 A	65 A
Power factor	>0.99 (0.8 leading - 0.8 lagging)		
THDi	<3%		
Efficiency			
Max. efficiency	97.8%		
EU efficiency	97.3%		
Protection			
DC reverse-polarity protection	Yes		
Short circuit protection	Yes		
Output over current protection	Yes		
Surge protection	DC Type II / AC Type II		
Grid monitoring	Yes		
Anti-islanding protection	Yes		
Temperature protection	Yes		
Strings monitoring	Yes		
I/V Curve scanning	Yes		
Integrated AFCI (DC arc-fault circuit protection)	Yes ⁽¹⁾		
Integrated PID recovery	Optional		
Integrated DC switch	Optional		
General Data			
Dimensions (W*H*D)	647*629*252 mm		
Weight	37 kg		
Topology	Transformerless		
Self-consumption (night)	<1 W		
Operating ambient temperature range	-25 ~ +60°C		
Relative humidity	0-100%		
Ingress protection	IP66		
Cooling concept	Intelligent redundant fan-cooling		
Max. operation altitude	4000 m		
Grid connection standard	G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC60068, IEC 61683, EN 50530		
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4		
Features			
DC connection	MC4 connector		
AC connection	OT terminal		
Display	LCD		
Communication	RS485, Optional: Wi-Fi, GPRS		

(1) Activation required.